

### **SINGLE SPAN**



A single span unit can span up to 120'. Designed to CSA specifications these units are quick and easy to install to provide safe access across.

# A multiple span unit is made up of as many single span units bolted together to cover the span required.



# **ENVIRONMENTAL BRIDGES**



Low profile, simple span steel units can quickly be put in place to provide quick access.



#### INSTALLATION


### **PORTABLE BRIDGES, ABUTMENTS AND WING WALLS**

#### EXAMPLE A




Installation where creeks and banks are solid and bridge embankments or piles are not needed.

#### EXAMPLE B



With timber embankments tied down to deadman as in Example A.

#### EXAMPLE C




Multiple span using portable bridge embankment FACE FRAMES and WINGS for the banks.

# **TECHNIQUES**

#### PORTABLE BRIDGES, ABUTMENTS AND WING WALLS


Sixty foot SIMPLE SPAN is winched aboard a flatbed trailer.



With site prepared, bridge is placed in position with the aid of a hoe or additional bedtruck.



A plan view of a typical single span installation, including JIMBOB EMBANKMENT FACE FRAMES and WING WALLS.







#### **BRIDGE INSTALLATION**







Jimbob Bridges are built to CSA W59.1 specification standards. They are engineered, insured and bonded.

 ABUTMENT PERMANENT PILING INSTALLATION

PILINGS FOR ABUTMENT

ABUTMENT WITH WING WALL

#### SIMPLE SPAN

- 1. Design Live Load CS750 truck plus impact.
- 2. Design Specification S6-88 except deflection limitation.
- 3. Material: Rolled sections to CSA G40.21 Grade 44W, pipe sections to ASTM A53 Grade B, HSS sections to CSA G40.21 Grade 50W
- 4. Weld to CSA W59.1
- 5. Bridge to be supported at end diaphragm and tied back to the abutment with cables at the 8"  $\phi$  pipe before opening to traffic.
- 6. Timber material to be species Group D or better.



# As well as installation, we provide total packages including:

- Transportation
- Engineering
- All permits
- Hydrology
- Site Preparation
- Supervision



#### **CORPORATE HEAD OFFICE:**

4923 - 43 STREET

**BOX 339** 

**ROCKY MOUNTAIN HOUSE, AB T4T 1A3** 

PH. 403.845.3285

FAX 403.845.6145

Email info@jimbobrentals.com

1.866.845.3285